

Nextiva S1970e

Compact, DVD-Quality Ethernet Video Server

The Nextiva™ S1970e Ethernet video server is a single-port, DVD-quality encoder designed for digital video monitoring and surveillance over IP networks.

The S1970e can deliver 4CIF, 30 Frames Per Second (FPS) for single-camera applications requiring optimal image quality. With MPEG-4 SP video compression, dynamic bandwidth allocation, and dual streaming capabilities, the Nextiva S1970e helps optimize use of valuable network resources. And the S1970e is built for ease of use, enabling up to five authorized users to simultaneously monitor live video and configure other unit settings using Internet Explorer and a secure and intuitive Web browser interface.

Easy to Configure and Manage

Nextiva Control Center, an easy-to-use management portal, simplifies deployment and enables the Nextiva S1970e to be configured and administered from a single location and application. Nextiva HealthCheck™ continuously monitors the performance of the S1970e, with automated diagnostics and problem correction for greater uptime and lower service costs. The Nextiva S1970e can also be configured and managed using Verint® nDVR™, Loronix Video Manager™, or from a Web browser.

Built on accepted industry standards for easy interoperability with existing IT infrastructure and video equipment, the Nextiva S1970e is a comprehensive video encoder solution designed to deliver superior functionality, long-term investment protection, and value.

Verint. Powering Actionable Intelligence.®

Verint Systems (NASDAQ: VRNT) is a leading global provider of analytic software-based solutions for communications interception, networked video, and business intelligence. Verint solutions transform voice, video, and text into *actionable intelligence* – timely, mission-critical insights for achieving strategic goals.

Since 1994, Verint has been committed to developing innovative solutions that help our customers achieve their most important objectives. Today, more than 1000 organizations in over 50 countries use Verint's actionable intelligence solutions to enhance security, boost operational efficiency, and fuel profitability.



KEY FEATURES

- ✓ DVD-quality, single-port encoder
- ✓ Dual streaming, MPEG-4 SP compression, and dynamic bandwidth allocation to optimize network use
- ✓ SSL-based authentication for enhanced security
- ✓ RS-422/485 serial port to support motorized domes and cameras
- ✓ Ethernet 10/100Base-T interface
- ✓ Standards based and firmware upgradeable for investment protection
- ✓ Automated configuration, health monitoring, and diagnostics with Nextiva

Nextiva Intelligent Edge Devices address security and performance challenges across a wide range of environments and applications.

The Nextiva S1970e features DVD-quality images and secure Web video streaming for single-camera applications.

VERINT
POWERING ACTIONABLE INTELLIGENCE®

Technical Specifications

NETWORK

Interface	Ethernet 10/100Base-T
Connector	RJ-45 jack
Protocols	Transport: RTP/IP, UDP/IP, TCP/IP, or multicast IP Others: DNS, NTP, HTTP, FTP, and DHCP client
Security	SSL-based authentication

VIDEO

Output	1 composite, 1 Vpp into 75 ohms (NTSC/PAL)
Dual Stream	4CIF, 30 FPS and CIF, 15 FPS programmable
Connector	BNC female
Compression	MPEG-4 SP
Resolution	Scalable from 176x128 to 704x480 pixels NTSC and 176x144 to 704x576 pixels PAL
Frame Rate	1-30 FPS programmable (full motion)
Bandwidth	Configurable 30 kbps to 6 mbps

SERIAL PORT

Electrical Levels	422/485 2/4 wires
Connectors	5 position terminal strip
Operating Mode	Transparent serial port supporting any asynchronous serial protocol

ALARM

Alarm	Input: 1 dry contact Output: 1 optically isolated relay contact (48V AC/DC at 100 mA max.)
Alarm Connector	5-position terminal block

AUDIO

Bi-directional Audio	Input: -46 to -3 dBV into 30 kOhm (line or microphone input) Output: -46 to -3 dBV into 16 ohms min.
Audio Connectors	1/8 in. (3.5 mm) stereo jacks

POWER

Supply Voltage	12V DC \pm 10% (4.3W)
Power Supply	Included

PHYSICAL

Dimensions	4.2 x 3.5 x 1.7 in. (106 x 90 x 42 mm)
Weight	9.2 oz (260 g)
Environmental	32°F to 122°F (0°C to 50°C)
Humidity	95% non-condensing at 122°F (50°C)

MANAGEMENT

Configuration	Nextiva, nDVR, Loronix Video Manager, SConfigurator, or Internet Explorer 6.0
Firmware Upgrade	Flash memory for upgrade of video codec and application firmware over the network

CERTIFICATION AND REGULATION

USA	FCC part 15 (subpart B, class A)
Canada	ICES-003/NMB-003
Europe	CE marked, EN 55022: 1998 class A, EN 55024

MODELS

S1970e-T	Compact, DVD-quality Ethernet video server with 1 bi-directional audio channel; power supply included
S1970e-T-XT	With 1 bi-directional audio channel and extended temperature range (-30 to +60°C); power supply included

WARRANTY

3-year limited warranty, covering parts and labor

Contact your Verint representative for specific configurations, ordering codes, and pricing information.

By providing this document, Verint Systems Inc. is not making any representations regarding the correctness or completeness of its contents and reserves the right to alter this document at any time without notice.

All marks referenced herein with the ® or TM symbol are registered trademarks or trademarks of Verint Systems Inc. or its subsidiaries. All rights reserved. All other marks are trademarks of their respective owners.

© 2006 Verint Systems Inc. All rights reserved.

Email: videosales@verint.com

Phone: 1-866-NEXTIVA

Or on the web at: www.verint.com/videosolutions

330 South Service Road, Melville, NY 11747 USA

July 2006

VERINT
POWERING ACTIONABLE INTELLIGENCE®